

CARACAL<sup>®</sup>



PRODUCT SHOWCASE



## PRODUCT SHOWCASE

ENHANCED F PISTOL / QUICK SIGHT SYSTEM	03
ENHANCED F PISTOL / 3-DOT SIGHTS	04
ENHANCED F PISTOL / SUPPRESSOR READY	05
CAR816 A2 RIFLE (16") 5.56MM	07
CAR816 A2 RIFLE (14.5") 5.56MM	08
CAR816 A2 PISTOL (14.5") 5.56MM	09
CAR816 A2 RIFLE (11.5") 5.56MM	10
CAR816 A2 PISTOL (11.5") 5.56MM	11
CAR814 A2 MOE RIFLE (16") 5.56MM	13
CAR814 A2 MOE RIFLE (14.5") 5.56MM	14
CAR814 A2 MOE RIFLE (11.5") 5.56MM	15
CAR814 A2 PATROL RIFLE (16") 5.56MM	16
CAR814 A2 PATROL RIFLE (16") .300 AAC BLACKOUT	17
CAR814 A2 PATROL RIFLE (14.5") 5.56MM	18
CAR814 A2 PATROL PISTOL (14.5") 5.56MM	19
CAR814 A2 PATROL RIFLE (11.5") 5.56MM	20
CAR814 A2 PATROL PISTOL (11.5") 5.56MM	21
CAR814 A2 PATROL RIFLE (7.5") .300 AAC BLACKOUT	22
CAR814 A2 PATROL PISTOL (7.5") .300 AAC BLACKOUT	23
CAR814 A2 VERSUS™ COMPETITION RIFLE (18") .223 WYLDE	24





## ENHANCED F PISTOL

The Enhanced F is a polymer framed, striker fired pistol chambered in 9mm. Designed for military and law enforcement duty use as well as, concealed carry and self-defense. Caracal's signature low-profile, low-mass, two-piece slide design combined with an intuitive grip angle, smooth crisp trigger press and strong tactile reset make this pistol effortless to shoot and manipulate for the novice, to the professional end user.

Continuing to build on the military and LE pedigree of Caracal International, The Caracal USA Enhanced F is designed and built to exacting standards and test protocols in order to provide relentless reliability, durability and accuracy, while maintaining cost efficiency and end user serviceability.

The Enhanced F is available in a variety of configurations and color combinations to suit the tastes of today's consumers, as well the needs of our modern-day soldiers and law enforcement officers.

Made in the USA! Backed by a lifetime warranty.

# ENHANCED F

9MM STRIKER-FIRED PISTOL WITH QUICK SIGHT™ SYSTEM



## TECHNICAL SPECIFICATIONS

**Caliber:** 9x19mm Parabellum

**Slide Length:** 7" (178mm)

**Barrel Length:** 4.1" (105.4mm)

**Height:** 5-5/16" (135mm)

**Width:** 1-3/32" (28mm)

**Weight:** 1 lbs. 12 oz. (790g)

**Magazine Capacity:** 18 rounds / 10 rounds

**Grip Frame:** Polymer

**Trigger System:** Short Double Action

**Trigger Pull (Constant):** 5.0 lbs. (2.2kg)

**Trigger Travel (constant):** 5/16" (8mm)

**Internal Safety (drop and striker safety):** 2

**Cocking Indicator:** 1

**Magazine Release:** Ambidextrous

**Options:** Front contrast sight, and front night sight

## KEY FEATURES

- Quick Sight™ System places both front and rear sights on a single focal plane, enabling the shooter to acquire a much faster flash sight picture.
- Designed for smooth-handling, accurate shooting, and low felt-recoil.
- Metal parts receive QPQ nitriding with an enclosed post-oxidizing surface treatment to protect against rust and wear and increase durability.
- Trigger shoe, trigger safety and trigger bar combine into a one-piece multi-function unit (MFU) designed to create an extremely intuitive pistol for shooters of all skill levels.
- Barrels SAAMI proof tested for +P ammunition.



# ENHANCED F

9MM STRIKER-FIRED PISTOL WITH 3-DOT SIGHTS



## TECHNICAL SPECIFICATIONS

**Caliber:** 9x19mm Parabellum

**Slide Length:** 7" (178mm)

**Barrel Length:** 4.1" (105.4mm)

**Height:** 5-5/16" (135mm)

**Width:** 1-3/32" (28mm)

**Weight:** 1 lbs. 12 oz. (790g)

**Magazine Capacity:** 18 rounds / 10 rounds

**Grip Frame:** Polymer

**Trigger System:** Short Double Action

**Trigger Pull (Constant):** 5.0 lbs. (2.2kg)

**Trigger Travel (constant):** 5/16" (8mm)

**Internal Safety (drop and striker safety):** 2

**Cocking Indicator:** 1

**Magazine Release:** Ambidextrous

**Options:** Contrast sights, night sights, and suppressor ready

## KEY FEATURES

- Designed for smooth-handling, accurate shooting, and low felt-recoil.
- Barrels SAAMI proof tested for +P ammunition.
- Metal parts receive QPQ nitriding with an enclosed post-oxidizing surface treatment to protect against rust and wear and increase durability.
- Standard 3-dot dovetail sights.
- Trigger shoe, trigger safety and trigger bar combine into a one-piece multi-function unit MFU designed to create an extremely intuitive pistol for shooters of all skill levels.

# ENHANCED F

9MM STRIKER-FIRED PISTOL SUPPRESSOR-READY



## TECHNICAL SPECIFICATIONS

<b>Caliber:</b> 9x19mm Parabellum
<b>Slide Length:</b> 7" (178mm)
<b>Barrel Length:</b> 4.6" (118mm)
<b>Height:</b> 5-5/16" (135mm)
<b>Width:</b> 1-3/32" (28mm)
<b>Weight:</b> 1 lbs. 12 oz. (790g)
<b>Magazine Capacity:</b> 18 rounds / 10 rounds
<b>Grip Frame:</b> Polymer
<b>Trigger System:</b> Short Double Action
<b>Trigger Pull (Constant):</b> 5.0 lbs. (2.2kg)
<b>Trigger Travel (constant):</b> 5/16" (8mm)
<b>Internal Safety (drop and striker safety):</b> 2
<b>Cocking Indicator:</b> 1
<b>Magazine Release:</b> Ambidextrous
<b>Options:</b> Tritium Night Sights

## KEY FEATURES

- Suppressor height sights with optional Tritium night sight inserts, and a threaded barrel with knurled thread protector.
- Designed for smooth-handling, accurate shooting, and low felt-recoil.
- Metal parts receive QPQ nitriding with an enclosed post-oxidizing surface treatment to protect against rust and wear and increase durability.
- Trigger shoe, trigger safety and trigger bar combine into a one-piece multi-function unit (MFU) designed to create an extremely intuitive pistol for shooters of all skill levels.
- Barrels SAAMI proof tested for +P ammunition.



## CAR816 A2

The CAR816 A2 is a short stroke, push rod gas piston operated rifle chambered in 5.56x45mm NATO. Originally designed for dedicated military use, it has been tested and proven above and beyond the standards set by NATO for military small arms. Regarded as the next evolution in the short stroke piston rifle design, the Caracal® CAR816 A2 is lighter, faster, and slimmer than other offerings in this category.

Following the company mission statement, the CAR816 A2 is designed and built with a focus on safety, durability, and reliability. Utilizing only the best components and materials, rigorous testing protocols, and a dedication to craftsmanship, Caracal USA can provide, what we believe to be is the most reliable, dependable and durable short stroke piston rifle available today.

The CAR816 A2 is available in various configurations and colors ranging from 11.5" to 16" rifles, as well as 11.5" and 14.5" pistol configurations.

Made in the USA! Backed by a lifetime warranty.





# CAR816 A2

5.56MM GAS PISTON RIFLE (16")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- 5.56x45mm NATO Gas Operated Short Stroke Piston with 3 Position Adjustable gas key.
- QPQ BCG, Caracal® Anti-Tilt Carrier with Carpenter 158 Bolt.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and enhanced bolt catch.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Piston

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock expanded):** 36.3" (922mm)

**Overall Length (stock collapsed):** 33" (838mm)

**Barrel Length:** 16" (406mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 7.4 lbs. (3.3kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Caracal® 9.1" with M-LOK®, integrated QD

**Buttstock:** Magpul® STR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR816 A2

5.56MM GAS PISTON RIFLE (14.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- 5.56x45mm NATO Gas Operated Short Stroke Piston with 3 Position Adjustable gas key.
- QPQ BCG, Caracal® Anti-Tilt Carrier with Carpenter 158 Bolt.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and enhanced bolt catch.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Piston

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock expanded):** 34.5" (876mm)

**Overall Length (stock collapsed):** 31.2" (792mm)

**Barrel Length:** 14.5" (368mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 7.2 lbs. (3.2kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Caracal® 9.1" with M-LOK®, integrated QD

**Buttstock:** Magpul® STR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR816 A2 PISTOL

5.56MM GAS PISTON PISTOL (14.5")

## KEY FEATURES

- 5.56x45mm NATO Gas Operated Short Stroke Piston with 3 Position Adjustable gas key.
- Caracal<sup>®</sup> 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok<sup>®</sup> attachment system.
- SB Tactical - SBA3 Pistol Brace on Mil-Spec Buffer Tube - 6 position.
- QPQ BCG, Caracal<sup>®</sup> Anti-Tilt Carrier with Carpenter 158 Bolt.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and enhanced bolt catch.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Piston

**Modes of Fire:** Safe and Semi

**Overall Length (stock expanded):** 32.8" (833mm)

**Overall Length (stock collapsed):** 30.2" (767mm)

**Barrel Length:** 14.5" (368mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.9 lbs. (2.7kg)

**Trigger Type:** EDT<sup>®</sup> Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Caracal<sup>®</sup> 9.1" with M-LOK<sup>®</sup>, integrated QD

**Buttstock:** SBA3 Pistol Brace

**Grip:** Caracal<sup>®</sup>



# CAR816 A2

5.56MM GAS PISTON RIFLE (11.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- 5.56x45mm NATO Gas Operated Short Stroke Piston with 3 Position Adjustable gas key.
- QPQ BCG, Caracal® Anti-Tilt Carrier with Carpenter 158 Bolt.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and enhanced bolt catch.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Piston

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock expanded):** 31.5" (800mm)

**Overall Length (stock collapsed):** 28.2" (716mm)

**Barrel Length:** 11.5" (292mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 7 lbs. (3.4kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Caracal® 9.1" with M-LOK®, integrated QD

**Buttstock:** Magpul® STR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR816 A2 PISTOL

5.56MM GAS PISTON PISTOL (11.5")

## KEY FEATURES

- 5.56x45mm NATO Gas Operated Short Stroke Piston with 3 Position Adjustable gas key.
- Caracal<sup>®</sup> 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok<sup>®</sup> attachment system.
- SB Tactical - SBA3 Pistol Brace on Mil-Spec Buffer Tube - 6 position.
- QPQ BCG, Caracal<sup>®</sup> Anti-Tilt Carrier with Carpenter 158 Bolt.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and enhanced bolt catch.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Piston

**Modes of Fire:** Safe and Sem

**Overall Length (stock expanded):** 27.3" (693mm)

**Overall Length (stock collapsed):** 24" (609mm)

**Barrel Length:** 11.5" (292mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.5 lbs. (2.9kg)

**Trigger Type:** EDT<sup>®</sup> Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Caracal<sup>®</sup> 9.1" with M-LOK<sup>®</sup>, integrated QD

**Buttstock:** SBA3 Pistol Brace

**Grip:** Caracal<sup>®</sup>



## CAR814 A2

The CAR814 A2 is a direct impingement gas operated rifle, chambered in 5.56x45mm NATO or .300 Black Out. Designed and engineered in accordance to NATO standards. Originally designed for law enforcement and military applications. Using high quality components, advanced engineering and state of the art manufacturing processes, the CAR814 A2 is built to exacting tolerances to provide the end user with a durable, reliable and accurate weapon system.

This rifle is available in multiple configurations ranging from our "MOE" line, to our "PATROL" line of rifles. The MOE designation overlays the standard, non-free float barrel configurations with lengths ranging from 11.5" to 16". These MOE rifles are built to the same exacting NATO standards as all of our duty firearms and are tailored to meet the needs of militaries and LE agencies. No bells, no whistles, just unrelenting performance at a price that is hard to match.

The CAR814 A2 PATROL line of rifles share all the same fundamental traits of the other CAR814 A2 rifles, but also feature; free float barrels, low profile gas blocks, ambidextrous charging handles and fire controls as well as an "Enhanced Duty Trigger". These rifles are tailored to more specialized units within the military and LE communities as well as the discerning tastes of the commercial end user. The PATROL line of products are available in rifle and pistol configurations from 7.5" to 16" chambered in .300Blk and 11.5" to 16" chambered in 5.56x45mm.

Made in the USA! Backed by a lifetime warranty.



# CAR814 A2

5.56MM DIRECT IMPINGEMENT RIFLE (16")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- MagPul® MOE® Handguard with Mlok® attachment system, MagPul® CTR Buttstock, and flip-up rear sight.
- QPQ 4150 CMV Barrel with Caracal® Barrel Extension and Chamber Design.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Caracal® Forged 7075 Hard Coat Anodized upper and lower receiver set with integrated flared magazine well.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock expanded):** 35.8" (909mm)

**Overall Length (stock collapsed):** 32.5" (825mm)

**Barrel Length:** 16" (406mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.8 lbs. (3.0kg)

**Trigger Type:** MilSpec

**Trigger Pull:** 5.5 - 9.5 lbs. (2.5 - 4.3kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Magpul® MOE® with M-LOK®

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR814 A2

5.56MM DIRECT IMPINGEMENT RIFLE (14.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- MagPul® MOE® Handguard with M-LOK® attachment system, MagPul® CTR Buttstock, and flip-up rear sight.
- QPQ 4150 CMV Barrel with Caracal® Barrel Extension and Chamber Design.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Caracal® Forged 7075 Hard Coat Anodized upper and lower receiver set with integrated flared magazine well.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock expanded):** 34.5" (876mm)

**Overall Length (stock collapsed):** 31.2" (792mm)

**Barrel Length:** 14.5" (368mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.5 lbs. (2.9kg)

**Trigger Type:** MilSpec

**Trigger Pull:** 5.5 - 9.5 lbs. (2.5 - 4.3kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Magpul® MOE® with M-LOK®

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®





# CAR814 A2

5.56MM DIRECT IMPINGEMENT RIFLE (11.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- MagPul<sup>®</sup> MOE<sup>®</sup> Handguard with Mlok<sup>®</sup> attachment system, MagPul<sup>®</sup> CTR Buttstock, and flip-up rear sight.
- QPQ 4150 CMV Barrel with Caracal<sup>®</sup> Barrel Extension and Chamber Design.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Caracal<sup>®</sup> Forged 7075 Hard Coat Anodized upper and lower receiver set with integrated flared magazine well.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock expanded):** 31.5" (800mm)

**Overall Length (stock collapsed):** 28.2" (716mm)

**Barrel Length:** 11.5" (292mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.5 lbs. (2.9kg)

**Trigger Type:** MilSpec

**Trigger Pull:** 5.5 - 9.5 lbs. (2.5 - 4.3kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** Magpul<sup>®</sup> MOE<sup>®</sup> with M-LOK<sup>®</sup>

**Buttstock:** Magpul<sup>®</sup> CTR<sup>®</sup> Carbine Stock (Milspec)

**Grip:** Caracal<sup>®</sup>



# CAR814 A2 PATROL

5.56MM DIRECT IMPINGEMENT RIFLE (16")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 12" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- Magpul® CTR Buttstock on Milspec buffer tube - 6 position .
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock extended):** 35.8" (909mm)

**Overall Length (stock collapsed):** 32.2" (818mm)

**Barrel Length:** 16" (406mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.4 lbs. (2.9kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 12" Free Float with M-LOK® and QD points

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR814 A2 PATROL

.300 AAC BLACKOUT DIRECT IMPINGEMENT RIFLE (16")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 12" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- Magpul® CTR Buttstock on Milspec buffer tube - 6 position .
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** .300 AAC Blackout

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock extended):** 35.8" (909mm)

**Overall Length (stock collapsed):** 32.2" (818mm)

**Barrel Length:** 16" (406mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:6" (1:152mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.4 lbs. (2.9kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 12" Free Float with M-LOK® and QD points

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR814 A2 PATROL

5.56MM DIRECT IMPINGEMENT RIFLE (14.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 12" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- Magpul® CTR Buttstock on Milspec buffer tube - 6 position .
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock extended):** 34" (863mm)

**Overall Length (stock collapsed):** 31" (787mm)

**Barrel Length:** 14.5" (368mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6.2 lbs. (2.8kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 12" Free Float with M-LOK® and QD points

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR814 A2 PATROL

5.56MM DIRECT IMPINGEMENT PISTOL (14.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal<sup>®</sup> 12" Handguard with key lock anti-cant, integrated QD sling points and Mlok<sup>®</sup> attachment system.
- SB Tactical - SBA3 Pistol Brace on Mil-Spec Buffer Tube - 6 position.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi

**Overall Length (stock extended):** 32.7" (831mm)

**Overall Length (stock collapsed):** 30.3" (768mm)

**Barrel Length:** 14.5" (368mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6 lbs. (2.7kg)

**Trigger Type:** EDT<sup>®</sup> Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 12" Free Float with M-LOK<sup>®</sup> and QD points

**Buttstock:** SBA3 Pistol Brace

**Grip:** Caracal<sup>®</sup>



# CAR814 A2 PATROL

5.56MM DIRECT IMPINGEMENT RIFLE (11.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- Magpul® CTR Buttstock on Milspec buffer tube - 6 position .
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock extended):** 31" (787mm)

**Overall Length (stock collapsed):** 28" (711mm)

**Barrel Length:** 11.5" (292mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 6 lbs. (2.7kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 9" Free Float with M-LOK® and QD points

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®



# CAR814 A2 PATROL

5.56MM DIRECT IMPINGEMENT PISTOL (11.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 9" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- SB Tactical - SBA3 Pistol Brace on Mil-Spec Buffer Tube - 6 position.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** 5.56x45mm NATO

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi

**Overall Length (stock extended):** 30" (762mm)

**Overall Length (stock collapsed):** 27.8" (704mm)

**Barrel Length:** 11.5" (292.1mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:7" (1:178mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 5.8 lbs. (2.6kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Aluminum

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 9" Free Float with M-LOK® and QD points

**Buttstock:** SBA3 Pistol Brace

**Grip:** Caracal®



# CAR814 A2 PATROL

.300 AAC BLACKOUT DIRECT IMPINGEMENT RIFLE (7.5")

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal® 6" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- Magpul® CTR Buttstock on Milspec buffer tube - 6 position .
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.

## TECHNICAL SPECIFICATIONS

**Caliber:** .300 AAC Blackout

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi, or optional Select Fire

**Overall Length (stock extended):** 27.3" (692mm)

**Overall Length (stock collapsed):** 24" (609mm)

**Barrel Length:** 7.5" (190mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:5" (1:127mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 5.5 lbs. (2.5kg)

**Trigger Type:** EDT® Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 6" Free Float with M-LOK® and QD points

**Buttstock:** Magpul® CTR® Carbine Stock (Milspec)

**Grip:** Caracal®





# CAR814 A2 PATROL

.300 AAC BLACKOUT DIRECT IMPINGEMENT PISTOL (7.5")

## TECHNICAL SPECIFICATIONS

**Caliber:** .300 AAC Blackout

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi

**Overall Length (stock extended):** 26" (660mm)

**Overall Length (stock collapsed):** 23.2" (589mm)

**Barrel Length:** 7.5" (190mm)

**Barrel Contour:** Modified M4

**Barrel Material:** 4150 CMV, QPQ Black Nitride

**Rifling Twist:** 1:5" (1:127mm)

**Flash Hider:** A2 Style - 1/2"-28 Threads

**Weight w/o Magazine:** 5.5 lbs. (2.5kg)

**Trigger Type:** EDT<sup>®</sup> Sharp Shooter

**Trigger Pull:** 5.5 lbs. (2.5kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 6" Free Float with M-LOK<sup>®</sup> and QD points

**Buttstock:** SBA3 Pistol Brace

**Grip:** Caracal<sup>®</sup>

## KEY FEATURES

- Built to exceed NATO test protocols; Bore Obstruction and "Over the Beach" Testing.
- Caracal<sup>®</sup> 6" Handguard with key lock anti-cant, integrated QD sling points and Mlok<sup>®</sup> attachment system.
- SB Tactical - SBA3 Pistol Brace on Mil-Spec Buffer Tube - 6 position.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Enhanced Duty Trigger, Ambi Selector, stakeless end plate with integrated QD point, and latchless charging handle.



# VERSUS™

.223 WYLDE DIRECT IMPINGEMENT RIFLE (18")

## KEY FEATURES

- Proof Research 18" Carbon Fiber Barrel. 60% lighter than steel barrel with similar contour.
- Caracal® ultra light 15" Handguard with key lock anti-cant, integrated QD sling points and Mlok® attachment system.
- Mil-Spec BCG (Auto) with Carpenter 158 Bolt and Staked Gas Key.
- Geissele Super 3 Gun (S3G) trigger.
- Mission First Tactical Minimalist Buttstock, Oversized mag release, and stakeless ratcheting end plate with integrated QD sling point.

## TECHNICAL SPECIFICATIONS

**Caliber:** .223 Wylde

**Operating Principle:** Gas Operated, Direct Impingement

**Modes of Fire:** Safe and Semi

**Overall Length (stock extended):** 38" (965mm)

**Overall Length (stock collapsed):** 34.7" (881mm)

**Barrel Length:** 18" (457mm)

**Barrel Contour:** Medium / .750"

**Barrel Material:** 416R Stainless, Carbon Fiber Wrapped

**Rifling Twist:** 1:8" (1:203mm)

**Muzzle Device:** 2-Port, Self-timing muzzle brake

**Weight w/o Magazine:** 6.2lbs (2.8kg)

**Trigger Type:** Geissele S3G

**Trigger Pull:** 4lbs (1.8kg)

**Magazine Type:** Polymer with Steel Feed Lips

**Magazine Capacity:** 30 rounds / 10 rounds

**Hand Guard:** 15" Free Float with M-LOK® and QD points

**Buttstock:** Minimalist, 6- Position

**Grip:** Caracal®



Travis Gibson, Team Caracal USA

## **VERSUS™**

The VERSUS™ rifle was design by competitive shooters, for competitive shooters, with features that today's top competitors demand. By focusing on the essential aspects of dependability, accuracy, reduced weight, and superior ergonomics, the VERSUS™ Competition Rifle gives you the perfect foundation for your podium finish. This rifle provides a true "out of the box" solution for any competitor ranging from novices to World Class shooters, at a price point that allows everyone to run with the pack.

Made in the USA! Backed by a lifetime warranty.



CARACAL USA  
6051 W CORPORAL LANE  
BOISE, IDAHO 83704

(208) 323.8727

CARACALUSA.COM

     @CARACALUSA